

HULK[®] SERIES RAIL LIFT

L I F T P R O D U C T S S P E C I F I C A T I O N S

Design Highlights

- Low Profile for Surface-mounted Applications
- No Pit Construction Required
- Three-sided Platform
- Heavy-duty I-beam Deck Understructure
- Excellent End-load Stability in Fully Raised Position
- Displacement style Cylinder with Internal Stops
- Self-contained Power Unit/control Panel
- Standard Pre-wired Control Panel
- NEMA 4X Push-button Controller with 15' Cord
- Superior Speed-to-horsepower Ratio Compared to Scissor-style Dock Lifts
- Direct thrust Cylinder Provide Constant Speed Through Full Range of Travel
- Checker Plate or Smooth Deck Surface
- Sealed Guide Bearing Rollers
- Fused 24-volt Control Circuit
- 18" Bridge
- 30" Stationary Ramp with Lagging Angles
- Bolt On Handrail
- Hydraulic System Pressure Gauge

Project Information

Job Name _____
Address _____
General Contractor _____
Distributor _____
Model _____ Quantity _____ Voltage/Phase _____



Available Options

- Upper Travel Limit Switch
- In Motor Warning Beeper and Flashing Light on a Post X 60" High or Wall Mounted on Bracket
- Interlocking Gate
- Aluminum Bridges
- Larger Steel Bridges
- Power Pack Cover
- Other _____



ENTRE//MATIC

HULK[®] SERIES RAIL LIFT

L I F T P R O D U C T S S P E C I F I C A T I O N S

| Model No. | Lift Capacity [lbs.] | Deck Size [in] | Feet Per Minute [FPM] | HP | Ship. Weight [lb] |
|-----------|----------------------|----------------|-----------------------|----|-------------------|
| KRL45-4 | 4,000 | 48 x 60 | 13 | 5 | 2,050 |
| KRL46-4 | 4,000 | 48 x 72 | 13 | 5 | 2,200 |
| KRL55-4 | 4,000 | 60 x 60 | 13 | 5 | 2,150 |
| KRL56-4 | 4,000 | 60 x 72 | 13 | 5 | 2,500 |
| KRL57-4 | 4,000 | 60 x 84 | 13 | 5 | 2,650 |
| KRL58-4 | 4,000 | 60 x 96 | 13 | 5 | 2,800 |
| KRL66-4 | 4,000 | 72 x 72 | 13 | 5 | 2,800 |
| KRL67-4 | 4,000 | 72 x 84 | 13 | 5 | 2,950 |
| KRL68-4 | 4,000 | 72 x 96 | 13 | 5 | 3,100 |
| KRL610-4 | 4,000 | 72 x 120 | 13 | 5 | 3,300 |
| KRL612-4 | 4,000 | 72 x 144 | 13 | 5 | 3,600 |
| KRL45-6 | 6,000 | 48 x 60 | 12 | 5 | 2,200 |
| KRL46-6 | 6,000 | 48 x 72 | 12 | 5 | 2,400 |
| KRL55-6 | 6,000 | 60 x 60 | 12 | 5 | 2,400 |
| KRL56-6 | 6,000 | 60 x 72 | 12 | 5 | 2,750 |
| KRL57-6 | 6,000 | 60 x 84 | 12 | 5 | 2,875 |
| KRL58-6 | 6,000 | 60 x 96 | 12 | 5 | 3,000 |
| KRL66-6 | 6,000 | 72 x 72 | 12 | 5 | 3,100 |
| KRL67-6 | 6,000 | 72 x 84 | 12 | 5 | 3,250 |
| KRL68-6 | 6,000 | 72 x 96 | 12 | 5 | 3,400 |
| KRL610-6 | 6,000 | 72 x 120 | 12 | 5 | 3,700 |
| SRL612-6 | 6,000 | 72 x 144 | 12 | 5 | 3,900 |



ENTRE/MATIC

1612 Hutton Drive, Suite 140 ▾ Carrollton, TX 75006, USA ▾ Tel: 800-558-6960 ▾ Fax: 972-389-4766 ▾ Email: sales@kelleycompany.com ▾ www.kelleycompany.com
 A continuing research program is in effect at Kelley. We reserve the right to incorporate product improvement at any time without prior notice.

© 2013 4Front Engineered Solutions, Inc.

Form # KPS-LDRL-1213