



Armorguard™ Dock Seal with Head Pad

Product Specifications



DESIGN HIGHLIGHTS

- Exclusive SHARC™ (Super High Abrasion Resistant Compound) fabric on wear faces. Full height on side pads and full width on head pad
- Exclusive WearMaster® head pad helps defend against damage from yard spotters and air ride suspension trailers
- Exclusive roll-formed, galvanized steel framing
- Exclusive heat-sealed, full length, yellow guide stripes
- Endurance tested foam core is continuously bonded to frame surface with flexible, nonflammable adhesive
- Highly resilient, open-celled polyurethane foam keeps original shape and compresses easily to extend the seal life
- Side pad bottoms are tapered to avoid pinching and wear
- All pads are vented for air and moisture release
- Heavy-duty, galvanized steel mounting brackets included

APPLICATION DATA

Door width: _____ ft. _____ in. Door height: _____ ft. _____ in.
Dock height: _____ ft. _____ in. Bumper protection*: _____ in.
(*Includes bumper projection and any building wall/foundation offset or cantilever)

TRUCKS AND TRAILERS SERVICED




Width: _____ Max. _____ Min.
Height: _____ Max. _____ Min.
Length: _____ Max. _____ Min.
Hydraulic tailgate: ☐ Yes ☐ No Rear step section: ☐ Yes ☐ No
Tailgate/step section size: _____ in Yard jockeys: ☐ Yes ☐ No

PROJECT INFORMATION

JOB NAME _____
ADDRESS _____
GENERAL CONTRACTOR _____
DISTRIBUTOR _____
QUANTITY _____

CERTIFIED FOR CONSTRUCTION

BY _____
COMPANY _____
ADDRESS _____
DATE _____



Quantity _____

WearMaster® Head Pad Width: _____ (Total inches)

WearMaster® Head Pad Back/Face: ☐ 12/12 ☐ 18/18 ☐ 24/24 ☐ 12/15 ☐ 12/18

Drop Curtain: ☐ None ☐ 12" ☐ 18" ☐ 24" ☐ Velcro strips ☐ Full width

Side Pad Height: _____ (Total inches)

Side Pad Back/Face: ☐ 12/12 ☐ 6/10 ☐ 8/12 ☐ 10/12 ☐ 10/15 ☐ 8/15 ☐ 12/15 ☐ 10/18 ☐ 6/14

Base Material: 22 oz. black vinyl standard

Taper: ☐ Tapered ☐ Non-Tapered

Top Projection: ☐ 8" ☐ 10" ☐ 12" ☐ 14" ☐ 16" ☐ 18" ☐ 20" ☐ 22" ☐ 24"

Bottom Projection: ☐ 8" ☐ 10" ☐ 12" ☐ 14" ☐ 16" ☐ 18" ☐ 20" ☐ 22" ☐ 24"

Bottom Flaps: 3" Inside standard

Blockout: ☐ None ☐ Top projection _____" ☐ Bottom projection _____"

Wear Face: Full height side pad & full width head pad with SHARC fabric standard, black

Reinforced Inside Face: Full height side pad with SHARC fabric standard, black

Options: ☐ Door numbers

Side Pad Mounting Brackets: ☐ None ☐ Flats & angles ☐ Angles ☐ 1 1/2" Offsets & Angles

*Conversions: To convert measurements to metric, see formulas below:

Inches x 25.4 = millimeters (Example: 4" x 25.4 = 101.6 mm)

Feet x .3048 = meters (Example: 12' x .3048 = 3.66 m)



Kelley
1612 Hutton Drive, Suite 140
Carrollton, TX 75006
800.558.6960
www.kelleydocksolutions.com

4Front Engineered Solutions reserves the right to change specifications and designs without notice and without incurring obligations. 4Front Engineered Solutions products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Kelley as word and logo are registered trademarks belonging to ASSA ABLÖY Entrance Systems AB or other companies controlled by the same organization. All rights reserved.

©ASSA ABLÖY. All rights reserved. Part of ASSA ABLÖY. Printed in USA. KPS-SEAHP-1220